

# DYROS 6

Brass connectors with 6 mm passage capacity\* for water, grease, air, oil etc. ....

- developed specifically for coolants in plastic tools




Today Dyros 6 can be found everywhere:


- on plastic moulds
- on compressed-air plants
- on oxygen and gas cylinders
- in operating rooms and in numerous other places




In short, Dyros can be found wherever small dimensions, reliability and safety are a must.


All connectors have built-in valves that are perfectly tight even at very low pressure.

A locking device is automatically released upon engagement, so that the connector can be operated by one hand.

Safety connectors with hose fitting		3/8" (9,5 <sup>0</sup> )	1/2" (12,7 <sup>0</sup> )			
Straight				Art. No. SLK 616	Art. No. SLK 618	
				Art. No. SVK 616/90		
				Art. No. SVK 616/45		

Safety connectors with internal thread		BSP1/4"	BSP3/8"	M14x1.5	M16x1.5
Straight		Art. No. SLKR 614 (HEX = 17)	Art. No. SLKR 638 (HEX = 20)	Art. No. SLKM 645 (HEX = 17)	Art. No. SLKM 665 (HEX = 20)

Safety connectors with external thread		BSP1/4"	BSP3/8"	M14x1.5	M16x1.5
Straight		Art. No. SLKUR 614 (HEX = 17)	Art. No. SLKUR 638 (HEX = 17)	Art. No. SLKUM 645 (HEX = 17)	Art. No. SLKUM 665 (HEX = 17)
		Art. No. SVKUR 614/90	Art. No. SVKUR 638/90	Art. No. SVKUM 645/90	Art. No. SVKUM 665/90
		Art. No. SVKUR 614/45	Art. No. SVKUR 638/45	Art. No. SVKUM 645/45	Art. No. SVKUM 665/45

Safety adaptor connector with nipple fitting		serie:	30	40	90
Straight			Art. No. SLK 600/300	Art. No. SLK 600/400	Art. No. SLK 600/900

## Dyros products are unimpeachable quality - down to the smallest detail

The Thread BSP corresponds to G1/4" - G3/8".

The connectors on these pages are also made without valve (OV).

All connectors can also be delivered with coloured red and blue caps.

Order e.g. with valve no. SLK 616  
Without valve order no. SLK 616OV

Order e.g. valve no. SLK 616R = red cap

