

DYROS 2000

3/4" hose connectors with 15 mm passage capacity for water, air and oil







Dyros 2000 hose connectors are used wherever big water capacity is needed

- in nurseries
- in fishing industry
- in dairy production
- on sea wessels etc.

The connectors are manufactured from solid brass and chromium plated. Stainless steel is used for locking balls and springs. O-ring seals are made of Nitril rubber (70NBR/99018) - especially resistant to water and will withstand temperatures from -30° til +100°C.

The nipples are held in the connector by three balls serving as a ball bearing which prevents the hose from kinking.

The Dyros 2000 selection handles most any situation and as soon as new applications are found, the system is adjusted and - if necessary - extended.

Connector with internal thread		BSP 3/4"		Nipple with internal thread		BSP 1/2"		BSP 3/4"			
		Art.No. 2113				Art.No. 2211	Art.No. 2213				
Connector with external thread		BSP 1/2"		BSP 3/4"		Nipple with external thread		BSP 1/2"		BSP 3/4"	
		Art.No. 2121	Art.No. 2123					Art.No. 2221	Art.No. 2223		
Connector with hose fitting		3/4"		Nipple w. hose fitting		1/2" (12,7°)		5/8" (16°)		3/4" (19°)	
		Art.No. 2133				Art.No. 2231	Art.No. 2232	Art.No. 2233			